Product Data Sheet



AROMA SIGNATURE STYLE

Technical Data				
Туре	1007-04			
Power rating	1520	[W]		
Stand-by power	< 0.5	[W]		
Voltage	220 - 240	[V]		
Frequency	50 / 60	[Hz]		
Weight	2.8	[kg]		
Weight with packaging	3.6	[kg]		
Height x Width x Depth	355 x 325 x 155	[mm x mm x mm]		
Height x Width x Depth packaging	365 x 373 x 203	[mm x mm x mm]		
Water tank volume	1.25	[]		
Maximum amount of coffee	10 / 1.12	[cups]/[1]		
Brewing time	05:50	[mm:ss]		
Finish brew coffee	85	[°C]		
Warmkeeping temperature	85	[°°]		
Automatic shut-off time	30/60/90	[h]		
Filter size	1x4			
Feature Details				
Glass jug				
- dishwasher safe				
- stainless steel neck strip				
- removable lid				
- high polished stainless steel jug handle cover				
Water tank	-			
- water level indication for 2 to	10 cups			
- additional markings for 0.25l,		nd 1.25l		
- removable water tank lid				
- water tank lid with high polished stainless steel application				
			es off at end of the brewing cycle	
Filter	on, owneries on whe	an initig the watertarik, switch		
- break-proof				
- drip stop				
- dishwasher safe				
- filter size 1x4				
- high polished stainless steel handle cover				
- lock-in mechanism for fixing at the coffeemaker, to be opened by one hand operation at the handle				
- removable filter lid for easy cle	zailliy			
Housing				
- high polished stainless steel		ingle remainship nexts for the		
- filter, filter lid, spout, water tank lid and jug lid as single removable parts for easy cleaning				
- spout with high polished stain	less steel cover			
Brewing system		reduced permitter O. F.	an aratian	
- 2 brewing modes: full power a				
- glass raising tube for visualiza	-	r during brewing or decalcifica	ation	
- separate 55W heater for warn	n keeping			
Water hardness setting				
- programmable water hardness: 1 (>21°dH), 2 (12°-20°dH), or 3 (0-12°dH)				
- water hardness setting shown by flashing LED				
Calcification indication				
- necessity to descale shown with red LED				
Descaling program				
- CALC button to start descaling program				
- decalcification process works with reduced power, audio indication when finished				
Brewing end signal				
- programmable acustic brewing end signal loudness: loud, less loud, off				
- factory setting: loud				

Product Data Sheet



AROMA SIGNATURE STYLE

Technical Data				
Туре	1007-04			
Power rating	1520 [W]	car = 10 (0.0 - 3		
Stand-by power	< 0.5 [W]	0.80 - 4		
Voltage	220 - 240 [V]			
Frequency	50/60 [Hz]			
Weight	2.8 [kg]			
Weight with packaging	3.6 [kg]			
Height x Width x Depth	355 x 325 x 155 [mm x mm x mm]			
Height x Width x Depth packaging	365 x 373 x 203 [mm x mm x mm]			
Water tank volume	1.25 [1]			
Maximum amount of coffee	10 / 1.12 [cups] / [l]			
Brewing time	05:50 [mm:ss]			
Finish brew coffee	85 [°C]			
Warmkeeping temperature	85 [°C]			
Automatic shut-off time	30/60/90 [h]			
Filter size	1x4			
Feature Details				
Automatic shut-off				
- programmable warm keeping	time: 30, 60, or 90 minutes			
- warm keeping time setting she	own by flashing LED			
- factory setting 30 minutes for	energy save behaviour			
ECO switch				
- separate On-Off-switch for tot	al shut-off of the coffeemaker			
Power cord				
- cord length 90 cm				
- storage under bottom cover				
- power cord outlet on the back	or on the side			
Approvals				
- Safety approval (VDE-GS)				
- Food law approval				
- ECBC approval (European Co	offee Brewing Centre)			