Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Markslöjd

Supplier's address: Markslöjd Intertrade AB, Gränevägen 5, 51162 Marks Kommun Skene Västra Götaland, SE

Model identifier: 108330

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	Soldered				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer Height	6	Spectral power	See image		
dimensions Width	70	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	70	range 250 nm to 800 nm, at full-load			
Claim of equivale	nt power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,438		
Parameters for LED and OLED light sources:						
R9 colour renderi	ng index value	7	Survival factor	1,00		
the lumen mainte	enance factor	0,96				
(2).						

(a)'-' : not applicable;

(b)'-' : not applicable;

